

**CARATTERISTICHE TECNICHE**

- * Motore C.V.E trifase IP55 Cl. F
- * Albero in acciaio rivestito in PVC
- * Girante in PVC
- * Lanterna PVC con supportazioe in Nylon

FX4

TIPO FX4	MOTORE HP	MOTORE KW	MOTORE R.P.M.	DIMENS. A	DIMENS. B	DIMENS. C	DIMENS. D	DIMENS. E	DIMENS. F	DIMENS. G	DIMENS. H	DIMENS. i
FX 4.8.03	0,08	0,06	1350	170	110	20	400	60	19	120	100	04/07
FX 4.12.03	0,12	0,09	1350	170	no	20	500	60	19	120	100	04/07
FX 4.17.03	0,17	0,12	1350	180	130	20	600	70	19	140	115	04/09
FX 4.25.03	0,25	0,18	1350	180	130	20	700	70	19	140	115	04/09
FX 4.35.03	0,35	0,25	1350	210	140	20	800	70	19	160	130	04/09
FX 4.50.03	0,5	0,37	1350	210	140	20	1000	70	19	160	130	04/09

FX6

TIPO FX6	MOTORE HP	MOTORE KW	MOTORE R.P.M.	DIMENS. A	DIMENS. B	DIMENS. C	DIMENS. D	DIMENS. E	DIMENS. F	DIMENS. G	DIMENS. H	DIMENS. i
FX 6.25.03	0,25	0,18	900	210	140	20	800	100	19	160	130	04/09/24
FX 6.35.03	0,35	0,25	900	210	140	20	1000	100	19	160	130	04/09/24

FX8

TIPO FX6	MOTORE HP	MOTORE KW	MOTORE R.P.M.	DIMENS. A	DIMENS. B	DIMENS. C	DIMENS. D	DIMENS. E	DIMENS. F	DIMENS. G	DIMENS. H	DIMENS. i
FX8.25.03	0,25	0,12	660	210	140	20	800	110	19	160	130	04/09/24